

**PRODUCT FEATURES:**

- For use as a front or backup camera.
- Wide angle lens for cross traffic viewing.
- With parking guide lines (can be turned on/off).
- Horizontal flip image feature for front camera use.
- Top or lip mount.



**PARTS INCLUDED:**



CTC-210 Camera



Extension Cable and Accessories

**WIRING DIAGRAM:**



\*NOTE: To power the camera, tap the RED wire to +12V and the BLACK wire to ground.

- 1) If tapping power from the radio or a backup camera interface, tap the RED wire to the camera output wire of the radio or interface. The BLUE wire is not used in this instance.
- 2) If you are tapping power from the backup light, tap the BLUE wire "B" to the +12V backup light wire then connect the BLUE wire "A" to the RED wire. Connect the black wire to ground.

**CROSS TRAFFIC VIEWING:**

The CTC-210 can be used as a backup camera or as a front camera with wide angle cross traffic viewing. The wide angle viewing aids when backing up and the driver has limited view of what's on the left or right of the vehicle. It can be top mounted or lip mounted and the viewing angle is also adjustable both vertically and horizontally. Loosen the camera lock ring and the ball camera can be turned 360 degrees. The CTC-210 has parking guide lines when used as a backup camera. To deactivate the parking guide lines, cut the thin GREEN wire on the 4 pin barrel connector. See diagram above. To use the CTC-210 as a front camera, cut the thin GREEN wire to remove the parking guide lines and cut the thin RED wire to flip the image horizontally.

