



Rear-View Integration Interface for MASERATI GRAN TURISMO 2008 - Up

Product Features

- Activates Reverse camera input.
- Adds three A/V Inputs.
- On-screen display setup.
- Switch the video sources via the OE buttons.

Vehicle Applications

MASERATI

2008 – Up

Gran Turismo

Connection Diagram



	1/6	Rev.120116
Crux Interfacing Solutions www.cruxinterfacing.com		tel. #: (818) 609-9299 fax #: (818) 996-8188





Rear-View Integration Interface for MASERATI GRAN TURISMO 2008 - Up

Wiring Instructions

1

3



Unplug OEM LVDS cable from the OEM monitor (which is connected to the Command box) and plug it into the LVDS INPUT of the LVDS Controller box.

Connect the LVDS cable supplied in the kit to the LVDS OUT of the RVCMT-69 and to the LVDS IN of the LVDS Controller box.

Connect the LCD cable supplied in the kit to the LVDS OUT of the LVDS controller box an into the OEM monitor.

Connecting the CAN Wires



1. Tap CAN HIGH (Brown/Green) from the Power harness to the CAN HIGH (Black/Pink) wire on the Command. 2. Tap CAN LOW(Green) from the Power harness to the CAN LOW (White/Pink) wire on the Command.

	2 / 6	Rev.120116
Crux Interfacing Solutions www.cruxinterfacing.com		tel. #: (818) 609-9299 fax #: (818) 996-8188





Rear-View Integration Interface for MASERATI GRAN TURISMO 2008 - Up

DIP Switch Settings

Disconnect power to the interface before setting the DIP switches.

DIP#	Function	Selection			
1		ON : Skip RGB Mode			
±		OFF : RGB Display			
n		ON : Skip A/V 1			
Z	AVVINUTE	OFF : A/V1 Display			
2		ON : Skip A/V 2			
Э	A/V Z WIUTE	OFF : A/V2 Display			
л	A/V 3 MUTE	ON : Skip A/V 3			
4		OFF : A/V3 Display			
5	Not Used				
6		Not Used			
7	DearMada	ON : Aftermarket Rear Camera			
/	Redi IVIOUE	OFF : OEM Rear Camera			
8	Not Used				

Remote Control Functions

	Function
POWER & PIP	No Function
MENU	Activate OSD menu
ОК	Make a selection, change image display
A	Move upward
▼	Move downward
<	Move left
	(press this button for more than 5 seconds to
	access to the factory mode)
•	Move right
	(press this button for more than 2 seconds to
	reset all the data about user environment)



	3/6	Rev.120116
Crux Interfacing Solutions www.cruxinterfacing.com		tel. #: (818) 609-9299 fax #: (818) 996-8188





Rear-View Integration Interface for MASERATI GRAN TURISMO 2008 - Up

OSD Settings

Analog RGB Mode:

Menu of IMAGE COLOR OSD UTIL	NAVI N BRIGHTNESS CONTRAST SHARPNESS USER IMAGE	NO INPUT	Menu of IMAGE COLOR OSD UTIL	NAVI RED GREEN BLUE USER COLOR	NO INPUT	Menu of IMAGE COLOR OSD UTIL	NAVI LANGUAGE TRANS H_POSITION V_POSITION	NO INPUT	Menu of IMAGE COLOR OSD UTIL	NAVI FACTORY I	NO INPUT RESET
MENU to	Return SEL	to Select	MENU to	Return SEI	L to Select	MENU to	Return SE	L to Select	MENU to	Return	SEL to Select

IMAGE

- BRIGHTNESS
- CONTRAST
- SHARPNESS
- USER IMAGE: (4 Color Options)

- RED: Adjust Red
- GREEN: Adjust Green
- BLUE: Adjust Blue
- USER COLOR:
 (User selectable
 option)

OSD

- LANGUAGE: Select
 desire language
- TRANS: Adjust Transparency
- H_POSITION / V_POSITION: Adjust OSD Screen Position

UTIL

 FACTORY RESET: Reset to Factory Default

Video Mode:

Menu of IMAGE OSD UTIL	AV1 BRIGHTNESS CONTRAST SATURATION HUE SHARPNESS USER IMAGE	NO INPUT	Menu of IMAGE OSD UTIL	AV1 LANGUAGE TRANS H_POSITION V_POSITION	NO INPUT	Menu of IMAGE OSD UTIL	AV1 FACTORY RI	NO INPUT SET
MENU to	Return SE	L to Select	MENU to	Return SE	L to Select	MENU to	Return S	SEL to Select

IMAGE

- BRIGHTNESS
- CONTRAST
- SATURATION
- HUE
- SHARPNESS
- USER IMAGE: (4 Color Options)

OSD

- LANGUAGE: Select
 desire language
- TRANS: Adjust Transparency
- H_POSITION: Move Screen Horizontally
- V_POSITION: Move Screen Vertically

UTIL

 FACTORY RESET: Reset to Factory Default

	4 / 6	Rev.120116
Crux Interfacing Solutions www.cruxinterfacing.com		tel. #: (818) 609-9299 fax #: (818) 996-8188



RVCMT-69

Rear-View Integration Interface for MASERATI GRAN TURISMO 2008 - Up

Monu of FACTORY MAGE H-POSITION PARK V-POSITION UTIL NAVI MODEL AVOUT SELECT	Monu of PACTORY MAGE PARK ENABLE PARK SETUP UTIL SAFE ENABLE	Menu of FACTORY IMAGE CALIBRATION PARK IR MEMORY UTIL DVD TYPE DTV TYPE JOG SHUTTLE FACTORY RESET FACTORY RESET
MENU to Return OK to Select	MENU to Return OK to Select	MENU to Beturn OK to Select

IMAGE

Adjusting the Position of the Navigation Screen

- H_POSITION: Move Screen Horizontally
- V_POSITION: Move Screen
 Vertically
- NAVI MODEL: Do Not Use
- AVOUT SELECT: Default, AV1, AV2, AV3

PARK

- PARK ENABLE: Enable/Disable
 Parking Guide Line
- PARK SETUP: Control the position of the parking Guide Line
- SAFE ENABLE: Turn ON or OFF
 VIM Feature

UTIL

- CALIBRATION: Do Not Use
- IR MEMORY: Do Not Use
- DVD TYPE: Setup DVD Type
- DTV TYPE: Setup DTV Type
- JOG SHUTTLE: Do Not Use
- FACTORY RESET: Reset all values to factory default



PARK

- PARK ENABLE: Enable/Disable
 Parking Guide Line
- PARK SETUP: Control the position of the parking Guide Line
- SAFE ENABLE: Turn ON or OFF VIM Feature



PARK – ENABLE

- A. With 'PARK ENABLE' set to ON, the Parking Guide Line will be shown on the screen.
- B. Press OK button on the remote and 'H_POS' will be shown on the right hand side of the screen. Move the screen horizontally to the desired position.



PARK ENABLE

A. Press OK button on the remote and 'V_POS' will be shown on the right-hand side of the screen. Move the screen Vertically to the desired position.

Crux Interfacing Solutions
www.cruxinterfacing.com



tel. #: (818) 609-9299 fax #: (818) 996-8188

Rev.120116



RVCMT-69

Rear-View Integration Interface for MASERATI GRAN TURISMO 2008 - Up

DVD Player Model Selection

Menu of FACTORY MAGE PARK UTIL DVD TYPE DTV TYPE DTV TYPE JOG SHUTTLE FACTORY RESET NEC/SANYO	Menu of FACTOR IMAGE PARK UTIL DVD TY JOG SH PACTOR DV-108	Y ATION DRY PE UTTLE UTTLE IY RESET	Menu of FACTORY IMAGE PARK UTIL DVD TYP JOG SHU FACTOR SANYO-1	TION RY PE JTTLE Y RESET
MENU to Return OK to Save Menu of FACTORY IMAGE PARK UTIL CALIBRATIC IR MEMORY DVD TYPE JOG SHUTY FACTORY R SANYO-2 MENU to Return	MENU to Return	OK to Save	MENU to Return Y ATION DRY PB PE UTTLE TY RESET OK to Save	ÓK to Save

UTIL – DVD TYPE

NEC/SANYO, DV-108, SANYO-1, SANYO-2, USER

If the DVD player you are using is not NECVOX or SANYO based, you will need to program the remote controller in the 'IR MEMORY' section and set the DVD TYPE to USER.

NOTE: If you program the remote in FACTORY Mode, the DVD type will automatically be saved under 'USER'.

SWC Controls

Press and hold the 'PHONE PICK UP' button on the Steering Wheel Controls for about 2 seconds. to toggle between the AV sources.

A short press will maintain its OEM function.



	6/6	Rev.120116
Crux Interfacing Solutions www.cruxinterfacing.com		tel. #: (818) 609-9299 fax #: (818) 996-8188