

AVIGM-04S + VCIP5

CHEVROLET:
2012 - 2014 Sonic
2012 - 2014 Spark

A/V INPUT INTEGRATION FOR SELECT CHEVROLET VEHICLES 2012-2014

We recommend reading this installation guide first before starting any work. Following these instructions from "Start" to "Finish" will ensure a smooth and hassle free installation. We offer telephone support M-F 9:00 AM - 5:00PM PDT at 1 (855) 822-1348. We are here to help.

PARTS INCLUDED:

- (1) GM-04S Interface
- (1) GM-04S Harness
- (1) GM-04S A/V Adaptor
- (1) VCIP5 (HDMI to Composite Cable)
- (1) Instruction

PRECAUTIONS:

- Remove the negative side of the battery to avoid any short circuits during the installation.
- Do not install the interface near any major components or near the HVAC system. This may cause damage or overheating to the vehicle.
- **Do not disconnect the airbag connection behind the radio panel.**

PRELIMINARY:

Please read the entire manual before installing this interface.

Vehicle must be equipped with factory DVD changer.

This interface does not activate DVD reader.

SAFETY WARNING:


THIS INTERFACE IS DESIGNED TO ACTIVATE VIDEO IN-MOTION TO ALLOW THE PASSENGER ACCESS TO THE ADDRESS INPUT WHILE THE VEHICLE IS IN-MOTION. THIS INTERFACE MAY CAUSE AN ERROR WHEN SERVICED AT THE OEM DEALER. BE AWARE THAT MOST DEALERS WILL ATTEMPT TO VOID THE MANUFACTURERS WARRANTY WHEN INSTALLING ANY AFTERMARKET EQUIPMENT. IMPROPER USE OF THIS INTERFACE BY THE DRIVER MAY RESULT IN CITATION. DRIVER MUST KEEP FULL ATTENTION ON THE ROAD AND RESPONSIBILITY ON THE SAFETY OF THEIR PASSENGERS.

INSTALLING THE INTERFACE:

1. Remove the factory radio to gain access to the factory connectors.
2. Remove the 40-Pin connector from behind the radio.
3. Make the T-Harness connections behind the factory radio.
(if the connectors do not match please contact tech support)
4. Set the dip switch to permanently activate the VIM feature.
5. Test the display while the car is in-motion to verify the VIM is active.


SETTING THE DIP SWITCHES

Dip 1: This dip switch is the permanent solution for keeping the VIM unlocked.




**ALL OTHER DIP SWITCHES
MUST BE SET TO OFF!**

INSTALLATION OVERVIEW




40-PIN
(male plug)

◀ **TO FACTORY
RADIO**



8-PIN
(male plug)



40-PIN
(female plug)

◀ **TO FACTORY
HARNESS**

SELECTING THE A/V INPUT

From the factory radio, once you plug in the A/V Input Adaptor, You will notice the radio activate the AUX (Movie) source.

With your composite device connected, begin watching your media to the factory display. The included VCIP5 allows you to mirror your image from your iPhone 5 to your factory screen.



TROUBLE SHOOTING

1. No video display while driving.
 - Make sure the dip switches are in the proper location.



**AVIGM-04S
+ VCIP5**

CHEVROLET:
2012 - 2014 Sonic
2012 - 2014 Spark

A/V INPUT INTEGRATION FOR SELECT CHEVROLET VEHICLES 2012-2014

ADDITIONAL ITEMS FOR AVIGM-04S



**8" NEW STYLE NAVIGATION RADIO
(1-PIECE RADIO)**

3.5mm A/V ADAPTOR (Included)



Using our 3.5mm A/V adaptor you are able to connect any composite output device to your factory screen.

Our new VCIP5 cable allows you to connect your iPhone 5 to the composite input, when using the Apple Lightning to HDMI adaptor (**Sold separately**)

When using our VCIP5 you will be able to mirror (one way) the display of your iPhone to your video screen. And all applications that allow you to rotate will fill the screen on the radio display.

