

Vehicle Applications

Mercedes Benz

2012-2014	C-Class	2013-2014	GLK
2013-2014	CLS	2012-2015	ML
2012-2015	E-Class	2012-2015	SL
2012-2015	G-Class	2012-2015	SLK
2013-2015	GL	2011-2013	SLS
2015-2015	GLA		

Notes

- The AVIMB-1 will enable the Auxiliary Audio/Video Input on the navigation radio menu.

Parts Included



Crux Interfacing Solutions 6860 Canby Avenue, Suite 116, Reseda, CA 91335



www.cruxinterfacing.com tel. #: (818) 609-9299 fax #: (818) 996-8188

rev.060215



continued

Installation Instructions

- 1. Locate OBD-port and remove cover (commonly located under the dashboard on the driver side).
- 2. Turn ignition switch to ACC.
- 3. Wait until the navigation has booted.
- 4. Plug coder into OBD-port.
- 5. The navigation will re-boot.
- 6. When the navigation startup-screen shows, remove coder from OBD-port.
- 7. Your radio's Auxiliary Audio / Video input feature is now enabled.
- 8. Plug the aqua blue FAKRA connector to the back of the display's green FAKRA socket.
- 9. Use a video RCA extension cable (not included) and plug it between the FAKRA to RCA video adaptor cable and the video source (i.e. DVD Player)
- 10. Plug the black audio connector harness behind the radio and plug in the audio source.

To remove the Auxiliary Audio/Video feature from the navigation's menu repeat steps 1-6. After the first use on a vehicle, the coder AVIMB-1 is personalized to this vehicle. On this vehicle the enabling and removing the audio/video feature can be repeated without limit.

Operation

- 1. Activating the Auxiliary Audio/Video Input feature on the radio will create an A/V AUX tab on the source drop down menu.
- 2. Plug in your external A/V source, ie. DVD player to the A/V input cable.
- 3. Using the Comand controller on the center console, go to the source menu and click on the A/V AUX tab.
- 4. Video will appear on the display and audio should be heard on the factory sound system.

2/2

rev.060215